Type	Spec	Pitch	Width	Radius(mm) / Height(mm)	Inside Height	Max. Size of Cable & Hose (mm)	Moving Speed	Material: Body	Material: Divider	Material: Separater	Material: End Bracket	Distance (단위/M): Short &Long	Distance (단위/M): Free Span	Distance (단위/M): Recommend Length	Page
HYBRID CABLE CARRIER	KHA91	91	100~600	200/510, 250/610, 300/710, 350/810, 400/910, 450/1,010, 500/1,110	70.5	65	5m/sec	ENG. Plastic	ENG. Plastic	Aluminum	Steel	Short Distance	3.6	4.2	판매중단
	KHA92	91	100~600	200/520, 250/620, 300/720, 350/820, 400/920, 450/1,020, 500/1,120	80	73	"	"	"	"	"		3.6	4.2	판매중단
	KH526/S	52.6	65 80 100 125 150 175 200 225 250	125/250, 175/250, 225/250, 275/250	47.9	43	"	"	"	ENG. Plastic	"	Long Distance	-	-	18
	KHA526/S	52.6	80~400	125/250, 175/250, 225/250, 275/250	49	43	"	"	"	Aluminum	"		-	-	20
	KHA91/S	91	100~600	200/300, 250/300, 300/300, 350/300, 400/300, 450/300, 500/300	70.5	65	"	"	"	"	"		-	-	22
	KHA92/S	91	100~600	200/300, 250/300, 300/300, 350/300, 400/300, 450/300, 500/300	80	73	"	"	"	"	"		-	-	24
PLASTIC COVER TYPE	KP16	15.6	10 15 25 40	18/49, 28/69, 38/89, 50/113	10	8	3m/sec	ENG. Plastic	x	x	ENG. Plastic	Short Distance	1.3	0.8	30
	KP20	20	15 25 30 40	18/56, 28/76, 37/94, 50/120	15	12	"	"	x	x	"		1.5	1.2	32
	KP32	32	15 25 35 50	28/82, 38/102, 50/126, 75/176, 100/226	20	16	"	"	x	x	"		1.8	1.9	34
	KP40	40	40 57 80 100	50/139, 75/189, 100/239, 125/289, 150/339, 200/439	25	22	5m/sec	"	ENG. Plastic	x	Steel & ENG		2	1.8	36
	KP454	45.4	40 57 80 100	48/138, 70/182, 90/222, 120/282, 145/332, 195/432	28	23	3m/sec	"	"	x	ENG. Plastic		1.5	1.7	38
	KP50	55.5	40 50 65 75 80 87 100 120 150 160 175 187 200	60/175, 75/205, 100/255, 125/305, 150/355, 200/455	32	28	"	"	"	Aluminum	Steel & ENG		2.3	2.8	40
	KSC588	58.8	50 65 75 80 87 100 120 150 160 175 187 200	68/186, 80/215.5, 100/254.7, 125/300.1, 150/356.2, 200/456	36.1	31	"	"	"	ENG. Plastic	Steel		2.5	2.5	42
	KDP070	70	65 75 80 87 100 120 150 160 175 187 200	75/215, 100/265, 130/325, 180/425, 230/525	40	36	"	"	"	Aluminum	"		2.7	2.7	44
	KSC715	71.5	65 80 100 125 150 175 200 225 250	80/230, 100/270, 125/320, 150/370, 200/470, 250/570	47.9	43	"	"	"	ENG. Plastic	"		3.3	2.5	46
	CDP080	80	100 150 200 250 300 350 400	150/376, 200/476, 250/576, 280/636, 400/876	49	45	5m/sec	"	"	x	"		3.2	3	48
	KP90	91	150 200 250 300 350 400	150/384, 200/484, 250/584, 300/654	54.5	50	"	"	"	Aluminum	"		4	3.3	50
	CDP091	91	100 150 200 250 300 350 400	150/384, 200/484, 250/584, 300/684	55	53	3m/sec	"	"	x	"		3.6	3.8	52
	CDP100	100	100 150 200 250 300 350 400	200/506, 250/606, 300/706, 350/806, 400/906, 500/1106	68	62	5m/sec	"	"	Aluminum	"		3.2	4.2	54
	KDP100	100	100 150 200 250 300 350 400	150/418, 200/518, 250/618, 300/718, 350/818, 400/918	85	78	"	"	"	"	Steel &ENG.		4.8	5	56
	KP357	35.7	52	75/196.9, 87/221.7, 100/248.4, 125/298.8, 150/348.7, 200/448.2	36.9	32	"	"	x	x	ENG. Plastic		2	2	58

LEVELTEC ENGINEERING PTY LTD - sales@leveltec.com.au - +61 2 6558 9264

Type	Spec	Pitch	Width	Radius(mm) / Height(mm)	Inside Height	Max. Size of Cable & Hose (mm)	Moving Speed	Material: Body	Material: Divider	Material: Separater	Material: End Bracket	Distance (단위/M): Short &Long	Distance (단위/M): Free Span	Distance (단위/M): Recommend Length	Page
ALUMINUM BAR TYPE	CDS070	70	80~400	75/215, 100/265, 130/325, 180/425, 230/525	40	36	3m/sec	ENG. Plastic	ENG. Plastic	Aluminum	Steel	Short Distance	2.8	2.5	62
	CDS080	80	80~400	150/376, 200/476, 250/574, 280/636, 400/876	47	43	5m/sec	"	"	"	"		3.2	3	64
	K90	91	100~600	150/384, 200/484, 250/584, 300/684	57	50	"	"	"	"	"		3.8	3.8	66
	CDS100	100	100~600	200/504, 250/604, 300/704, 350/804, 400/904, 500/1104	70.5	62	"	"	"	"	"		3.6	4.2	68
	CDS150	150	100~800	200/560, 300/760, 400/960, 500/1160, 600/1360	111	100	"	"	"	"	"		8.5	5	70
ENCLOSED TYPE	KM50	55.5	40, 65, 80	75/205, 100/255, 125/305, 150/355, 200/455	32	28	3m/sec	ENG. Plastic	X	X	Steel	Short Distance	2.3	2.5	74
	CDM050	50	40, 70	75/192, 100/242, 125/292, 150/342	21	17	"	"	"	"	"		2.4	1.8	판매중단
	KM715	71.5	75, 100, 120	100/270, 125/320, 150/370, 200/470, 250/570	45	41	"	"	ENG. Plastic	Aluminum	"		2.8	2.5	76
	CDM080	80	150, 200, 300	150/376, 200/476, 250/576, 280/636, 400/876	48	45	5m/sec	"	"	X	"		3.2	2.8	78
	KM90	91	150, 200	150/384, 200/484, 250/584, 300/684	54	50	"	"	"	Aluminum	"		3.8	3.5	80
	CDM091	91	150, 200, 250, 300	150/384, 200/484, 250/584, 300/684	55	51	3m/sec	"	"	ENG. Plastic	"		3.5	3.5	82
	CDM100	100	150, 200, 300	200/506, 250/606, 300/706, 350/806, 400/906, 500/1106	68	64	3m/sec	"	"	Aluminum	"		3.2	3.7	84
	KDM100	100	150, 200, 300	200/518, 250/618, 300/718, 350/818, 400/918	85	66	5m/sec	"	"	"	Steel &ENG.		4.5	4.5	86
CLEAN ROOM TYPE	KD20A	20	20, 40, 60	28/83, 38/103, 48/123	15	8	3m/sec	ENG. Plastic	X	X	ENG. Plastic	Short Distance	0.5	0.7	판매중단
	KD20B	20	20, 40, 60	28/83, 38/103, 48/123	20	8	"	"	X	X	"		0.5	0.7	판매중단
	KD30A	30	40, 56, 80, 100, 125, 150	45/135, 55/155, 75/195, 100/245, 125/295, 150/345	25	21	"	"	ENG. Plastic	Aluminum	"		0.7	0.9	판매중단
	KD30B	30	40, 56, 80, 100, 125, 150	45/157, 55/177, 75/217, 100/267, 125/317, 150/367	36	24	"	"	"	"	"		0.7	1.2	판매중단
	KD40	40	36, 52, 76, 96, 121, 146	75/241, 100/291, 125/341, 150/391, 200/491, 250/591	57	41	"	"	"	"	"		0.9	1.6	판매중단
	KA33	33.5	36, 52, 76, 96, 121, 146	55/168, 75/208, 100/258, 125/308, 150/358, 200/458	36	32	"	"	"	"	"		1.8	1.8	88

Type	Spec	Pitch	Width	Radius(mm) / Height(mm)	Inside Height	Max. Size of Cable&Hose (mm)	Moving Speed	Material: Body	Material: Divider	Material: Separater	Material: End Bracket	Distance (단위/M): Short&Long	Distance (단위/M): Free Span	Distance (단위/M): Recommend Length	Page
LONG DISTANCE PLASTIC TYPE	CDPS050	50	54 80	75/130 100/130 125/130 150/130	29	22	3m/sec	ENG. Plastic	x	x	Steel		-	20	판매중단
	KSC588/S	58.8	50 65 80 100 120 160 200	68/200 80/200 100/200 125/200 150/200 200/200	36.1	31	3m/sec	"	ENG. Plastic	ENG. Plastic	"		-	15	94
	KDPS070	70	65 75 80 87 100 120 150 160 175 187 200	75/230 100/230 130/230 180/230 230/230	40	36	"	"	"	Aluminum	"		-	35	96
	KSC715/S	71.5	65 80 100 125 150 175 200 225 250	80/250 100/250 125/250 150/250 200/250 250/250	47.9	43	"	"	"	ENG. Plastic	"		-	15	98
	CDPS080	80	100 150 200 250 300 350 400	150/250 200/250 250/250 280/250 400/250	49	45	5m/sec	"	"	x	"	Long Distance	-	60	100
	CDPS100	100	100 150 200 250 300 350 400	200/300 250/300 300/300 350/300 400/300 500/300	68	62	"	"	"	Aluminum	"		-	70	102
	CDMS100	100	150 200 300	200/300 250/300 300/300 350/300 400/300 500/300	68	62	"	"	"	"	"		-	60	104
	CDPR100	100	100 150 200 250 300 350 400	200/300 250/300 300/300 350/300 400/300	68	62	"	"	"	"	"		-	70	106
LONG DISTANCE ALUMINUM TYPE	SRS070	70	80~400	75/230 100/230 130/230 180/230 230/230	40	36	5m/sec	ENG. Plastic	ENG. Plastic	Aluminum	Steel		-	50	112
	SRS080	80	80~400	150/250 200/250 250/250 280/250 400/250	47	44	"	"	"	"	"		-	60	114
	SRS100	100	100~600	200/300 250/300 300/300 350/300 400/300 500/300	70.5	65	"	"	"	"	"		-	70	116
	SRS150	150	100~800	200/400 300/400 400/400 500/400 600/400	111	100	"	"	"	"	"	Long Distance	-	70	118
	WS080	80	80~400	150/250 200/250 250/250 280/250 400/250	47	44	"	"	"	"	"		-	60	120
	WS100	100	100~600	200/300 250/300 300/300 350/300 400/300 500/300	70.5	65	"	"	"	"	"		-	70	122
	WS150	150	100~800	200/400 300/400 400/400 500/400 600/400	111	100	"	"	"	"	"		-	70	124
STEEL 'S' TYPE	CDKS070	70	60~300	75/200 90/230 125/300 145/340 200/430	31	25	1m/sec	SPHC	ENG. Plastic	Aluminum	Steel		3.5	4	136
	CDKS095	95	100~400	125/320 145/360 200/470 250/570 300/670 400/870	48	42	"	"	"	"	"		5	5.2	137
	CDKS125	125	100~400	200/496 250/596 300/696 400/896	70	48	"	"	"	"	"		6	6.8	138
	CDKS130	130	100~400	200/496 250/596 300/696 400/896	70	48	"	"	"	"	"	Short Distance	6	6.8	139
	CDKS180	180	300~700	250/640 300/740 400/940 500/1140 600/1340 700/1540	113	86	"	"	"	"	"		8	8.5	140
	CDKS250	250	300~700	350/920 450/1120 600/1420 750/1720 1250/2720	183		"	"	"	"	"		9.5	10.5	141

Type	Spec	Pitch	Width	Radius(mm) / Height(mm)	Inside Height	Max. Size of Cable&Hose (mm)	Moving Speed	Material: Body	Material: Divider	Material: Separater	Material: End Bracket	Distance (단위/M): Short&Long	Distance (단위/M): Free Span	Distance (단위/M): Recommend Length	Page
STEEL 'H' TYPE	CDKH070	70	60~300	75/200, 90/230, 125/300, 145/340, 200/430			1m/sec	SPHC	x	x	Steel		3.5	4	144
	CDKH095	95	100~400	125/320, 145/360, 200/470, 250/570, 300/670, 400/870			"	"	x	x	"		5	5.2	145
	CDKH125	125	100~400	200/496, 250/596, 300/696, 400/896			"	"	x	x	"	Short Distance	6	6.8	146
	CDKH130	130	100~400	200/496, 250/596, 300/696, 400/896			"	"	x	x	"		6	6.8	147
	CDKH180	180	300~700	250/640, 300/740, 400/940, 500/1140, 600/1340, 700/1540			"	"	x	x	"		8	8.5	148
	CDKH250	250	300~700	350/920, 450/1120, 600/1420, 750/1720, 1250/2720			"	"	x	x	"		9.5	10.5	149
LONG DISTANCE STEEL 'S' TYPE LONG DISTANCE STEEL 'H' TYPE	CDKSL095	95	100~400	125/678, 145/740, 200/913, 250/1070, 300/1227, 400/1541	48	48	1m/sec	SPHC	ENG. Plastic	Aluminum	Steel	Long Distance	-	35.0	152
	CDKSL130	130	100~400	200/1200, 250/1300, 300/1500, 400/1800	70	42	"	"	"	"	"		-	30.0	153
	CDKHL095	95	100~400	125/678, 145/740, 200/913, 250/1070, 300/1227, 400/1541			"	"	x	x	"		-	35.0	154
	CDKHL130	130	100~400	200/1200, 250/1300, 300/1500, 400/1800			"	"	x	x	"		-	30.0	155

Click the link to contact us about cable carriers

sales@leveltec.com.au

LEVELTEC